

We have created the universal EasyPlant seeder in cooperation with a manufacturer with nearly 50 years of experience in the production of grain seeders and over 25 years of background in the construction of pneumatic precision seeders. We use proven sowing devices, working elements, controllers and other components of our partner, whose machines have sown on millions of hectares.



A universal seeder for grains, rapeseed and legumes

Standard equipment:

- 2 rows of double-disc coulters
- pressure of coulters regulated steplessly
- stepless gearbox
- gear drive from the supporting wheel using a chain drive
- three-position pin sowing devices (double-piece sowing wheels)
- precise adjustment of the sowing depth, adjustable steplessly on the seeder wheels
- copying and press unit (rubber press wheels)
- rear transport lighting
- mechanically adjustable spring harrow
- loading and inspection platform with steps
- supporting wheels



When introducing grain seeders to our range, we made sure that they were functional, as well as durable and easy to use. The applied solutions and components will make them serve their buyers for many years of operation, regardless of the working conditions in which they will have to operate.

At special request, the machine can be equipped with additional fertilizer spreading system.



A universal seeder for grains, rapeseed and legumes

Within the framework of optional equipment, the following are available:

- electrically switched tramlines
 - tramlines with a computer*
 - hydraulic pre-emergence tramlines
 - looseners of tractor traces (2 pcs.)
 - looseners of tractor traces (4 pcs.)
- *) it supports the filling level sensor of the seed hopper and optional pre-emergence paths.



Purpose:

EasyPlant grain seeder is intended for sowing grains, rapeseed, grasses and legumes. The machine can work solo or aggregated by means of a hydraulic coupling with active, disc and tine aggregates. EasyPlant seeder can work on any type of soil. Owing to the solid construction of our machine, sowing into stony or poorly cultivated fields is not a problem. Our seeder, as standard, is equipped with self-cleaning double-disc coulters, which allow sowing in cultivated soil as well as in a mulch. EasyPlant seeder, already in its standard version, has a very large seed hopper capacity.





Technical specifications	Unit	Model					
Operating width	m	2,5	2,7	3	3,5	4	
Weight	kg*	1120	1230	1320	1570	1800	
Number of coulters	(pcs.)	19	21	23	27	31	
Power demand	HP**	60-70	65-80	75-90	90-110	100-120	
Seed hopper capacity	l	780	850	940	1085	1250	
Working speed	km/h	5-8	5-8	5-8	5-8	5-8	
Working depth range	cm	0-12	0-12	0-12	0-12	0-12	

*) weight of the machine with standard equipment with rubber pressure wheels.
 **) minimum power demand may significantly vary depending on the equipment and soil conditions.

